Corning[®] Stripettor[™] Ultra Pipet Controller

Designed for comfort and sample safety



This light, ergonomic, motorized pipet controller is designed for use with glass and plastic serological pipets from 0.5 to 100 mL. Conveniently positioned switches change operating modes and speeds quickly to handle different liquid volumes and various viscosities. Aspirating and dispensing speed is controlled through the finger triggers. When fully charged, the batteries enable up to 8 hours of continuous use. The large LCD display clearly indicates battery status, pipetting mode, and speed.

Features

- LCD display for continuous visualization of speed, modes, and battery status
- ▶ Colored nose pieces for user or application identification
- Well-positioned function buttons
- 3-position charging stand











Charging position Rest position

Break position





Hydrophobic PTFE filters



Battery cover with wings



Extra nose pieces



3 position charging stand

Ordering Information

Corning® Stripettor™ Ultra Pipet Controller

4099	Corning Stripettor Ultra Pipet Controller, with universal power supply, three 0.2 μ m ³ colored nose pieces, wall hanger, and 3-position charging stand				
Accessories					
4991	Hydrophobic PTFE filter 0.2 μm (5 pcs)				
4992	Hydrophobic PTFE filter 0.45 μm (5 pcs)				
4993	Silicone pipet holder				
4994	Battery set, 3 x AAA, NiHM				
4995	Battery cover with wings				
4996	Universal power supply, 9V with set of adaptors (EU, US, UK, and AUS)				
4997	Colored nose pieces, set of 4 (orange, yellow, green, red)				
4998	Charging stand, 3-positions				

Related Products

Serological Pipets, Individually Wrapped, Paper/Plastic Wrap

Cat. No.	Capacity (mL)	Graduations (mL)	Negative Graduations (mL)	Color Strip	Qty/Pk	Qty/Cs
4485	1	1/100	0.2	Yellow	50	1,000
4486	2	1/100	0.2	Green	50	1,000
4487	5	1/10	2.5	Blue	50	200
4488	10	1/10	3.0	Orange	50	200
4489	25	2/10	10.0	Red	25	200
4490	50	1/2	10.0	Purple	25	100
4491	100	1/1	N/A	Aqua	10	100

Warranty/Disclaimer: Unless otherwise specified, all products are for research use only. Not intended for use in diagnostic or therapeutic procedures. Corning Life Sciences makes no claims regarding the performance of these products for clinical or diagnostic applications.

For additional product or technical information, visit www.corning.com/lifesciences or call 800.492.1110. Outside the United States, call +1.978.442.2200 or contact your local Corning sales office.

CORNING

Corning Incorporated Life Sciences

836 North St. Building 300, Suite 3401 Tewksbury, MA 01876 t 800.492.1110 t 978.442.2200 f 978.442.2476 www.corning.com/lifesciences

ASIA/PACIFIC Australia/New Zealand t 61 427286832 China t 86 21 3338 4338 f 86 21 3338 4300

t 91 124 4604000 f 91 124 4604099

Japan t 81 3-3586 1996 f 81 3-3586 1291 Korea t 82 2-796-9500 f 82 2-796-9300 Singapore t 65 6572-9740 f 65 6735-2913 Taiwan t 886 2-2716-0338 f 886 2-2516-7500

EUROPE CSEurope@corning.com France t 0800 916 882 f 0800 918 636 Germany t 0800 101 1153 f 0800 101 2427 The Netherlands t 020 655 79 28

All Other European Countries t +31 (0) 206 59 60 51 f+31 (0) 206 59 76 73

LATIN AMERICA grupoLA@corning.com Brasil t 55 (11) 3089-7400 Mexico t (52-81) 8158-8400