

Compact Distribution Terminal (CDT)



Compact Distribution Terminal (CDT)



Specifications

General Specifications

| | |
|--------------|----------------------|
| Access Type | Front access fixed |
| Application | Preterminated cables |
| Product Type | Terminals |

Temperature Range

| | |
|---------------------------------|----------------------------------|
| Temperature Range, Operation | -20 °C - 60 °C (-4 °F - 140 °F) |
| Temperature Range, Installation | -5 °C - 50 °C (23 °F - 122 °F) |
| Temperature Range, Storage | -25 °C - 70 °C (-13 °F - 158 °F) |

Design

| Part Number | Adapter Type Front | Fiber Count | Housing Material |
|-----------------|------------------------|-------------|------------------|
| S46998-Z104-A25 | SC, E2000 or LC Duplex | 12 | Aluminum |

Design Adapter

| Part Number | Adapter Type |
|-----------------|------------------------|
| S46998-Z104-A25 | SC, E2000 or LC Duplex |

Dimension

| Part Number | Height | Width | Depth |
|-----------------|--------|----------|-------|
| S46998-Z104-A25 | 35 mm | 122.5 mm | 38 mm |

Compact Distribution Terminal (CDT)



Ordering Information

| Part Number | Units per Delivery |
|-----------------|--------------------|
| S46998-Z104-A25 | 1/1 |



Corning Comunicacoes Opticas • Estrada do Camorim 633 • Jacarepagua CEP 22780-070 • Rio De Janeiro, RJ Brazil
+55 21 3416 5150 • FAX: +55 21 2441 2037 • www.corning.com/opcomm/csa

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.