

CCHE Panel, MTP



CORNING

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fiber panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the pre-connectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.

Features and Benefits

Designed to accommodate all industry-standard adapter types

Unique colour-coded connector labeling system

Universal approach is used

Available in 6-, 8- and 12-fiber count options in most adapter styles

Also available for copper modules 12-fibre ST® Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel

CCHE Panel, MTP



◆◆	
RoHS	◆◆◆◆◆◆◆◆RoHS 2011/65/EU

Temperature Range	
◆◆◆◆◆◆◆◆	-20 °C - 70 °C (-4 °F - 158 °F)

Design			
Part Number	◆◆◆◆◆◆◆◆	◆◆◆◆	◆◆◆◆
CCHE-CP48-E3	◆◆◆	48	4
CCHE-CP72-E3	◆◆◆	72	6
CCHE-CP96-E3	◆◆◆	96	8
CCHE-CPE4-E3	◆◆◆	144	12
CCHE-CP72-89	◆◆	72	6
CCHE-CP96-89	◆◆	96	8
CCHE-CPE4-89	◆◆	144	12

Design Adapter				
Part Number	◆◆◆◆◆◆◆◆	◆◆◆◆	◆◆◆◆◆◆◆◆	◆◆◆◆
CCHE-CP48-E3	◆◆◆	MTP®	◆◆◆◆	◆◆
CCHE-CP72-E3	◆◆◆	MTP®	◆◆◆◆	◆◆
CCHE-CP96-E3	◆◆◆	MTP®	◆◆◆◆	◆◆
CCHE-CPE4-E3	◆◆◆	MTP®	◆◆◆◆	◆◆
CCHE-CP72-89	◆◆	MTP®	◆◆◆◆	◆◆
CCHE-CP96-89	◆◆	MTP®	◆◆◆◆	◆◆
CCHE-CPE4-89	◆◆	MTP®	◆◆◆◆	◆◆

CCHE Panel, MTP



Dimension	
Part Number	◇◇
CCHE-CP48-E3	35 mm
CCHE-CP72-89	35 mm
CCHE-CP72-E3	35 mm
CCHE-CP96-89	35 mm
CCHE-CP96-E3	35 mm
CCHE-CPE4-89	35 mm
CCHE-CPE4-E3	35 mm



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • ◇◇
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.