

Compact Distribution Terminal (CDT)



Compact Distribution Terminal (CDT)



Specifications

◆◆◆◆	
◆◆◆◆	◆◆◆◆◆◆
◆◆	◆◆◆◆◆◆
◆◆◆◆◆	◆◆
◆◆◆◆◆	◆◆

Temperature Range	
◆◆◆◆◆◆◆◆	-20 °C - 60 °C (-4 °F - 140 °F)
◆◆◆◆◆◆◆◆	-5 °C - 50 °C (23 °F - 122 °F)
◆◆◆◆◆◆◆◆	-25 °C - 70 °C (-13 °F - 158 °F)

Design				
Part Number	◆◆◆◆	◆◆◆◆◆◆	◆◆◆◆◆	◆◆◆◆
CDT-35	48	◆◆◆◆◆◆◆◆(◆◆ 12 x M12 ◆◆◆ 3 x M20)	◆◆◆◆◆	24
S46998-Z104-A25	12		◆	

Design				
Part Number	◆◆◆	◆◆◆◆	◆◆◆◆◆◆◆◆	◆◆◆◆◆◆
CDT-35	24	2	◆◆◆◆◆◆◆◆	◆◆

Design			
Part Number	◆◆◆◆◆◆◆◆	◆◆◆◆◆◆	◆◆◆◆◆◆◆◆◆◆
CDT-35		48 ◆◆◆◆◆◆◆◆	24
S46998-Z104-A25	SC, E2000◆LC ◆◆		

Compact Distribution Terminal (CDT)



Design Adapter		
Part Number	◆◆◆◆◆◆◆◆	◆◆◆◆◆
CDT-35	◆◆	
S46998-Z104-A25		SC, E2000◆LC ◆◆

Dimension			
Part Number	◆◆	◆◆	◆◆
S46998-Z104-A25	35 mm	122.5 mm	38 mm
CDT-35	254 mm	180 mm	90 mm

Ordering Information

Part Number	◆◆◆◆◆◆	◆◆◆◆◆◆◆◆◆◆
CDT-35	CDT empty box with fiber management, no front panels, adapters and pigtails, no splice trays, 12 cable glands M12 and one M20	1/1
S46998-Z104-A25		1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • ◆◆
 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.