

Corning's new Single-Fibre Pushlok® Adapter reduces complexity and time to deploy a Fibre network by giving operators more flexibility when using single Fibre connectorized offerings. Preconnectorized drops can be extended by leveraging Corning's innovative Pushlok Technology to enable mating between two single-Fibre Pushlok connectors. When paired with Single-Fibre FlexNAP™ systems, tethers can be directly connected to a drop cable in rural environments bypassing the need for a traditional terminal approach that may be otherwise inefficient.

Designed for use in nearly every access network environment, this hardened coupler is small enough to be placed in existing handholes or pedestals, on building facades, or in aerial networks (pole- or strand-mount) with mounting features molded into the housing. The Single-Fibre Pushlok Adapter has two keyed ports each with a corresponding release button to disengage the connector. When inserting connectors in the Single-Fibre Pushlok Adapter, the ports provide an audible and physical positive feedback minimizing technician variation and potential damage due to mishandling.



## Features and Benefits

### Replaces Pushlok® terminal

For less dense or rural applications

---

### Lower installation costs and fastest customer connection

Increased connection

---

### Durability

Weather resistant and robust design

---

### Small form factor

Optimises space in pedestals/handholes

---

### Low profile

Discrete ports for single fiber adaptability

---

### Low insertion loss

Factory polished connector endfaces mate directly

---

## Specifications

### General Specifications

Product type	Fibre Optic Adapters
Environment	Outdoor

### Optical Specifications Connector

Part Number	Fibre category	Polish
ADAPTER-PUSHLOK-SF	Single-mode (OS2)	APC

### Mechanical Specifications Fanout Kit

Height	Depth	Width
28.5 mm	100 mm	28.5 mm

### Design Adapter

Part Number	Adapter style	Adapter housing material	Adapter housing colour
ADAPTER-PUSHLOK-SF	Standard	Plastic	Black

## Ordering Information

Part Number	Units per delivery	Packaging method
ADAPTER-PUSHLOK-SF	10/1	Box



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
 00 800 2676 4641 • FAX: • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.