

# Evolv® Test Jumper with Pushlok® Technology

CORNING

## Features and Benefits

### Flexible connector offerings

Enables direct connection to a variety of optical power meters for in-field testing

# Evolv® Test Jumper with Pushlok® Technology

CORNING

## Design

Part Number	Fibre count
D14401E31AJ003M	1
D15801E31AJ003M	1

## Optical Characteristics

Fibre category	OS2
Fibre Type	Single-mode (OS2) / 250 µm
Fibre code	E
Wavelengths	1310 nm / 1383 nm / 1550 nm
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.4 dB/km

## Specifications - Connector A

Connector type
Pushlok

## Specifications - Connector B

Connector type	Polish	Connector type
SC APC		Pushlok
SC	UPC	Pushlok

## Dimension

Length
3 m
3 m

# Evolv® Test Jumper with Pushlok® Technology

CORNING



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
00 800 2676 4641 • FAX: • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.