

EDGE™ Splice Cassette

The logo consists of a solid blue square with the word "CORNING" written in white, uppercase, sans-serif font centered within it.

EDGE™ Splice Cassettes provide the interface between the bulk fiber cable and the LC duplex jumpers that connect directly into the electronics. The fiber splice cassette includes a one meter bare ribbon (or twelve x 250 μm single fiber) pigtail, that is loaded within the fiber splice cassette, and can be mass-fusion spliced directly to either ribbon or loose fiber cable. The LC duplex adapters feature hinged VFL-compatible shutters that move up and out of the way when the connector is inserted.

EDGE™ Splice Cassette



Specifications

◆◆◆◆	
◆◆	◆◆◆◆
◆◆◆◆	◆◆◆
◆◆◆◆	◆

Temperature Range	
◆◆◆◆◆◆◆◆	-20 °C - 60 °C (-4 °F - 140 °F)
◆◆◆◆◆◆◆◆	-5 °C - 50 °C (23 °F - 122 °F)
◆◆◆◆◆◆◆◆	-25 °C - 70 °C (-13 °F - 158 °F)

Design				
Part Number	◆◆◆◆◆◆◆◆	◆◆◆◆	◆◆◆	◆◆◆◆◆◆◆◆
EDGE-CS12-AD-P00QE-CSP	12	12	12	◆◆◆◆◆◆LC◆◆
EDGE-CS12-AD-P00QM-CSP	12	12	12	◆◆◆◆◆◆LC◆◆
EDGE-CS12-AD-P00QU	12	12	12	◆◆◆◆◆◆LC◆◆
EDGE-CS12-AE-P00RE	12	12	12	◆◆◆◆◆◆LC◆◆
EDGE-CS12-AE-P00RM-CSP	12	12	12	◆◆◆◆◆◆LC◆◆
EDGE-CS12-AF-P00RE	12	12	12	◆◆◆◆◆◆LC◆◆
EDGE-CS12-AD-P00QJ		12		◆◆◆◆◆◆LC◆◆
EDGE-CS12-AE-P00RJ		12		◆◆◆◆◆◆LC◆◆

EDGE™ Splice Cassette



Design				
Part Number	□□□□□□□□	□□□□	□□□□	□□□□□□□□
EDGE-CS12-AD-P00QE-CSP	□□□	1	Telcordia □□□□□□□□ □	□□□□□□□
EDGE-CS12-AD-P00QJ	□□□			
EDGE-CS12-AD-P00QM-CSP	□□□	1	□□□□□□□□□□□□	□□□□□□□
EDGE-CS12-AD-P00QU	□□□	1	□□□□□□□□□□□□	□□□□□□□
EDGE-CS12-AE-P00RE	□□	1	Telcordia □□□□□□□□ □	□□□□□□□
EDGE-CS12-AE-P00RJ	□□			
EDGE-CS12-AE-P00RM-CSP	□□	1	□□□□□□□□□□□□	□□□□□□□
EDGE-CS12-AF-P00RE	□□	1	Telcordia □□□□□□□□ □	□□□□□□□

Design	
Part Number	□□□□□□□□ □
EDGE-CS12-AD-P00QE-CSP	EDGE™
EDGE-CS12-AD-P00QJ	EDGE™
EDGE-CS12-AD-P00QM-CSP	EDGE™
EDGE-CS12-AD-P00QU	EDGE™
EDGE-CS12-AE-P00RE	EDGE™
EDGE-CS12-AE-P00RJ	EDGE™

EDGE™ Splice Cassette



Design	
Part Number	□□□□□□ □
EDGE-CS12-AE-P00RM-CSP	EDGE™
EDGE-CS12-AF-P00RE	EDGE™

Design Adapter			
Part Number	□□□□	□□□□□□□□	□□□□□
EDGE-CS12-AD-P00QE-CSP	□□	□□□□	LC
EDGE-CS12-AD-P00QJ	□□	□□□□	LC
EDGE-CS12-AD-P00QM-CSP	□□	□□□□	LC
EDGE-CS12-AD-P00QU	□□	□□□□	LC
EDGE-CS12-AE-P00RE	□□	□□□□	LC
EDGE-CS12-AE-P00RJ	□□	□□□□	LC
EDGE-CS12-AE-P00RM-CSP	□□	□□□□	LC
EDGE-CS12-AF-P00RE	□□	□□□□	LC

Ordering Information

Part Number	□□□□□□□□
EDGE-CS12-AD-P00QE-CSP	1/1
EDGE-CS12-AD-P00QJ	1/1
EDGE-CS12-AD-P00QM-CSP	1/1
EDGE-CS12-AD-P00QU	1/1
EDGE-CS12-AE-P00RE	1/1
EDGE-CS12-AE-P00RJ	1/1
EDGE-CS12-AE-P00RM-CSP	1/1

EDGE™ Splice Cassette



Part Number	◇◇◇◇◇◇◇◇
EDGE-CS12-AF-P00RE	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • ◇◇
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.