Everon® Copper Datacom E100 Unshielded



Our Cat.5e copper interconnect products work together to provide an easy-to-use solution for deploying high-speed connections throughout a building. The RJ45 jack is a key component in this system.

The jack's two cable entry points help make installation simple. The traditional one-click design enables an easy, tool-less termination on cables, meeting industry performance standards.

Features and Benefits

Tool-less jack

Easy and quick to install - reliable connection The conductors are wired in a single operation

Two cable entry points

Less cable bending required - better compliance with minimum bend radius
Enables a wide range of cable routing options
Easy to use in tight spaces

Reusable

Jack can be reused even after wiring mistake

No untwisting of pairs before termination

Minimized stripping length - limited pair untwist - pairs kept together, no wire guide required

Clip-in mounting

Designed to fit many other accessories

Accepts solid and stranded conductors

Enables "jack-to-plug" cables to be manufactured using stranded conductors

Integral shutter

No additional shuttering required on faceplates

Family Spec Sheet China_AEN Page 1 | Revision Date 2025-05-25

Everon® Copper Datacom E100 Unshielded



Specifications

Mechanical Specifications	
Solid Wire Diameter	5 mm to 65 mm

Ordering Information

Part Number	Product Description	Units Per Delivery
FQ100020723	OCK5EUV, E100U, RJ45 Vol, Cat5e, BP480, white	Piece
FQ100027132	OCK5EU-BL8, E100UBL, RJ45 Vol, Cat5e, Bag/8, Blue	Piece
FQ100027140	OCK5EU-GN8, E100UGN, RJ45 Vol, Cat5e, Bag/8, Green	Piece
FQ100027157	OCK5EU-R8, E100URD, RJ45 Vol, Cat5e, Bag/8, Red	Piece
FQ100027165	OCK5EU-Y8, E100UYE, RJ45 Vol, Cat5e, Bag/8, Yellow	Piece
FQ100027173	OCK5EU-BK8, E100UBK, RJ45 Vol, Cat5e, Bag/8, Black	Piece
FQ100027181	OCK5EU-OR8, E100UOR, RJ45 Vol, Cat5e, Bag/8, Orange	Piece
FQ100027199	OCK5EU-AL8, E100UAL, RJ45 Vol, Cat5e, Bag/8, Almond	Piece
FQ100029302	OCK5EU8, E100UWH, RJ45 Vol, Cat5e, Bag/8, white	Piece



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.

Family Spec Sheet China_AEN Page 2 | Revision Date 2025-05-25