

# OptiTap® Test Jumpers

CORNING

As an Industry leader in optical connectivity products, Corning designs and manufactures the OptiTap™ to SC APC Test Jumper with factory-terminated, environmentally sealed and hardened connectors to allow testing of OptiSheath® MultiPort Terminals and OptiSheath® UCAO Terminals .

## Features and Benefits

Enables direct connection to optical power meters for in-field testing

---

Environmentally sealed connector housing permits rapid connection to external flush-mounted bulkhead adapters on terminals or closures. Terminal or closure entry is not required for drop cable installation.

# OptiTap® Test Jumpers

CORNING

## Temperature Range

◊◊◊◊◊◊◊◊	-40 °C - 70 °C (-40 °F - 158 °F)
◊◊◊◊◊◊◊◊	-40 °C - 70 °C (-40 °F - 158 °F)

## Design

Part Number	◊◊◊◊◊◊
434401E31AJ003M	1
435801E31AJ003M	1
435801G31AJ003M	1
436101E31AJ003M	1

## Optical Characteristics

◊◊◊◊◊	OS2
◊◊◊◊◊	Single-mode (OS2) / 250 µm
◊◊◊◊◊	E
◊◊◊	1310 nm / 1383 nm / 1550 nm
◊◊◊◊◊	0.4 dB/km / 0.4 dB/km / 0.4 dB/km



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • ◊◊  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.