

Pushlok[®] Connector Technology

Just the Technical Facts: Single and Multifibre

The newest component in Corning's hardened connector portfolio offers robustness and reliability in a very small package. Designed for use in FTTx access networks where space and speed of installation translate into savings, the Pushlok[®] connector enables faster connections with audible and tactile feedback upon insertion. Rugged yet small, the connector platform and associated terminals meet the same performance attributes of Corning's existing hardened connector portfolio.



Pushlok[®] Connector Technology | Just the Technical Facts

What is a Pushlok[®] connector?

The Pushlok connector is an entirely different hardened connector form-factor with a compact, durable, craft-friendly design. The single-fibre connector leverages an SC APC – compatible ferrule and is backward compatible with widely deployed, threaded OptiTap[®] ports with a field-installed adapter. It can also be converted for use with standard SC APC patch panels.

The multifibre connector uses an MTP[®] compatible ferrule with 4 to 12 fibre and is backward compatible with OptiTip[®] ports using an assembly.

Why was the Pushlok connector developed?

As wireline and wireless networks proliferate, new customer needs have emerged and driven design, including:

- Congested existing infrastructure assets smaller connectors translate into smaller terminals, allowing them to be placed in existing handholes and pedestals
- Increasing pole attachment concerns lightweight design allows for aerial suspension of terminals on its own stub tail with minimal hardware
- Skilled technician availability intuitive insertion and feedback without the need for specialised labor
- Customer aesthetic requirements more building owners and municipal permitting offices are challenging deployments because of aesthetics and space requirements

What are the benefits of Pushlok connectors?

Go smaller, go simpler, go faster, go anywhere is the premise for the suite of products associated with the Pushlok technology.

- Go smaller the small-form-factor of the connector (half the size of the OptiTap) enables terminals up to 4x smaller, significantly reducing new infrastructure pathway costs or enabling reuse of existing infrastructure assets
- Go simpler eliminate SKU complexity with OptiTap, OptiTip, and SC convertible accessories
- Go faster field-friendly connector mating allows technicians to push, click, and connect without fear of overor under-tightening traditional threaded ports in a fraction of the time
- Go anywhere beyond traditional buried or aerial deployments, the terminals are able to be placed on street furniture, inside lamppost monopoles, on building facades and areas where traditional terminals wouldn't fit or be aesthetically appealing

How rugged is the Pushlok connector?

The Pushlok connector has undergone rigorous testing to ensure excellent, long-term durability. Tested to Telcordia GR-3120 which includes freeze/thaw, immersion, crush, humidity, and sealing tests among others to subject the connector to virtually any and all challenges it may face in a real-world deployment. It is also rated to IP68, defined by the IEC and used by the National Electrical Manufactures Association (NEMA) to indicate its uninterrupted performance in high-pressure immersion environments.

Are you Corning connected? www.corning.com/emea/evolv

CORNING

Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, GERMANY +00 800 2676 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

Corning Optical Communications reserves the right to improve, enhance, and modify the features and specifications of Corning Optical Communications products without prior notification. A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020, 2024 Corning Optical Communications. All rights reserved. CRR-1882-A4-BEN / August 2024