



CORNING

Corning Outside Plant Loose Tube and Ribbon Cables

Fiber Count	ALTOS® Loose Tube	SST-Ribbon™/SST-UltraRibbon™	ALTOS Loose Tube	SST-Ribbon/SST-UltraRibbon
				
	Dielectric	Dielectric	Armored	Armored
12	012ZU4-T4F22D20	012ZC4-14100D53	012ZUC-T4F22D20	012ZC5-14100D53
24	024ZU4-T4F22D20	024ZC4-14100D53	024ZUC-T4F22D20	024ZC5-14100D53
36	036ZU4-T4F22D20	036ZC4-14100D53	024ZUC-T4F22D20	036ZC5-14100D53
48	048ZU4-T4F22D20	048ZC4-14100D53	048ZUC-T4F22D20	048ZC5-14100D53
72	072ZU4-T4F22D20	072ZC4-14100D53	072ZUC-T4F22D20	072ZC5-14100D53
96	096ZU4-T4722D20	096ZC4-14100D53	096ZUC-T4122D20	096ZC5-14100D53
144	144ZU4-T4722D20	0144ZC4-14100D53	144ZUC-T4122D20	0144ZC5-14100D53
216	216ZU4-T4722D20	216ZC4-14100D53	216ZUC-T4122D20	216ZC5-14100D53
288	288ZU4-T4722D20	288ZV4-14100D53	288ZUC-T4122D20	288ZV5-14100D53
432	432ZU4-T4722D20	432ZV4-14100D53	432ZUC-T4122D20	432ZV5-14100D53
576		576ZV4-14100D53		576ZV5-14100D53
864		864ZV4-14100D53		864ZV5-14100D53

 Denotes SST-UltraRibbon (288-864 F)

Details	SST-Ribbon™	SST-UltraRibbon™	ALTOS® Loose Tube
			
Fiber Counts Available	Up to 216 F	288-864 F	Up to 432 F
Minimum Bend Radius (Loaded/Installed)	10x/15x OD	15x/15x OD	10x/15x OD
Maximum Tensile Load (Long Term/Short Term)	200/600 lb		200/600 lb
Operating Temperature	-40°C to 70°C		-50°C to 70°C
NEC® Article 770 Compliant	Yes		Yes
ANSI/CEA S-87-640 Compliant	Yes		Yes
GR-20 Compliant	Yes		Yes
Fiber Size	250 µm		250 µm
Splicer Compatibility	Mass-fusion splicers		Single-fiber splicers
FastAccess® Technology	No		Yes, up to 288 F in dielectric; up to 72 F in armored; binderless* FastAccess technology up to 72 F
Duct Requirements	1.25-in duct		Dielectric and Lite armored cable: 1.25-in duct, up to 432 fibers
Armor Available	Yes		Yes
Fiber Count	12-216	288-864	12-432
Value	<ul style="list-style-type: none"> ▪ Facilitates fast installation and restoration with 12 fibers spliced simultaneously via mass fusion splicing ▪ Allows for highest fiber count of any cable ▪ Enables greater fiber density per cable and per duct 		<ul style="list-style-type: none"> ▪ Features an easy, peel-away cable jacket ▪ Lowers overall risk of harm to the installer and the fibers
Quick Facts	Ribbon stack comprised of 12-fiber ribbons helically rotated to create excess fiber length	Ribbon stack comprised of a combination of 12-, 24-, and 36-fiber ribbons helically stranded in a central tube	Most widely deployed cable design globally

* Corning's proprietary binderless FastAccess® technology refers to the combination of a Corning FastAccess technology jacket with an innovative technology used to bind cable construction through the manufacturing process, eliminating the use of binder yarns and waterblocking tapes.

Looking for more information? Visit the links below.

[SST Ribbon Product Portfolio](#)

[ALTOS Product Portfolio](#)

[SST-Ultra Ribbon Product Portfolio](#)

[Fiber Optic Cable Resource Center](#)

For additional field-level support, please contact your local sales engineer or our customer care team at 1-800-743-2675.



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC 28216 USA
 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

Corning Optical Communications reserves the right to improve, enhance, and modify the features and specifications of Corning Optical Communications products without prior notification. A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2020 Corning Optical Communications. All rights reserved. LAN-2767-AEN / May 2020